

E119



The E119 Subwoofer was developed to bolster the low-end of the E-Series line of products. The enclosure is loaded with a light weight, long excursion, 19" SD19 Kevlar Neodymium driver utilizing Adamson's Advanced Cone Architecture and Symmetrical Drive Technology. The driver employs a dual 5" voice coil for exceptional power handling, with a dual-spider suspension system for extra stability even under extreme excursion. It is mounted in an ultra-efficient front-loaded enclosure, designed to reproduce clean, musical low frequency information. Users will appreciate the lower fundamental notes of this design.

The cabinet construction uses marine grade birch plywood as well as aircraft grade steel and aluminum, and is equipped with four Speakon™ NL4 connectors, two parallel In/Out rear plugs and two dedicated cardioid input connectors in the front. The integrated rigging system allows for either 0° or 3° splay between adjacent cabinets. The E119 can travel on installed casters, or on a 3-high covered dolly.

Specifications

Frequency Range (+/- 3dB)	30 Hz - 60 Hz
Maximum Peak SPL **	138 dB
Components LF	SD19 19" Kevlar Neodymium Driver
Nominal Impedance LF	8 Ω
Power Handling (AES / Peak) LF	1600 / 6400 W
Connection	4x Speakon™ NL4: 2x Rear Parallel (Pins 1 +/-) and 2x Front Cardioid Input (Pin 2 to 1)
Height Front (mm / in)	572 / 22.5
Width (mm / in)	749 / 29.5
Depth (mm / in)	889 / 35
Weight (kg / lbs)	66.5 / 146.5
Supported Processing	Lake

**12 dB crest factor pink noise at 1m, half space, using specified processing and amplification

